






Project _____ Catalog # _____ Prepared by _____ Notes _____ Order # _____ Date _____

0-10V Commercial Downlight Power Adjustment + Color Mixing Temperature

4 Inch/6 Inch/8 Inch/10 Inch CCT & LUMEN ADJUSTABLE
LED COMMERCIAL DOWNLIGHT

DESCRIPTION

Direct LED replacement conventional recessed downlight. Field select from three lumen outputs using Select Drive technology with adjustable during 3-stage 50%, 75%, 100%, and three color temperature select in 3000/ 4000/ 5000K. Universal 120-277V, 50/60 Hz drivers available. Universal 0-10V drivers dimmable to 10% with low end cutoff. Die cast heat sink maximizes passive thermal management and achieves a L70 rated lifetime of 50,000 hours. UL Classified and Listed for wet locations. IC Rated for direct contact with insulation.



DIMENSION

Type	4inch	6inch	8inch	10inch
Length(Inch)	5.12	7.48	10.17	11.22
Wight(Inch)	5.12	7.48	10.17	11.22
Height(Inch)	2.84	4.17	4.37	5.05
Weight(LBS)	0.45	0.58	0.75	0.9

ORDERING INFORMATION

Series	HT-US-ICDDR4-815/277-30113-C03-0-V1 (30-50)	HT-US-ICDDR6-820/277-30113-C03-0-V1 (30-50)	HT-US-ICDDR8-827/277-30112-C03-0-V1 (30-50)	HT-US-ICDDR10-837/277-30111-C03-0-V1 (30-50)
CRI	80	80	80	80
Power	9/12/15W(Wattage Selectable)	12/16/20W(Wattage Selectable)	16/21/27W(Wattage Selectable)	22/29/37.5W(Wattage Selectable)
CCT	3000K/4000/5000K	3000K/4000/5000K	3000K/4000/5000K	3000K/4000/5000K
Lumens	810/1,080/1,350LM	1,140/1,520/1,900LM	1,600/2,100/2,700LM	2,300/3,000/3,700LM
Efficacy	90LM/W	95LM/W	100LM/W	105LM/W
Dimmable	0-10v	0-10v	0-10v	0-10v



17578 Rowland St., City of Industry, CA 91748

Email: support@runbisonlighting.com



SPECIFICATION FEATURES

5CCT

- 3 CCT - Select color temperature from 3000K soft white, 4000K cool white, or 5000K daylight for your environment.
- The CCT and light output switch is located on the back of fixture, easy to organize.

CONSTRUCTION & OPTICS

- Unit includes die-cast metal housing, LED array, heat sink, lens, foam gasket, baffle trim ring, safety cable with hook and junction box.
- High quality PC lens.
- Efficiency LED array.
- Diffuse for uniform illumination.
- Baffle trim reduces glare for soft, comfortable illumination
- *Optional PMMA lens available.

DRIVER

- 120 - 277V 60Hz universal input voltage
- 0 - 10v smooth flicker free deep dimming to 10%

MOUNTING

- Canless design, no can housing needed for the installation.
- Pre-installed torsion spring clips.
- Unit comes with wiring nuts, no electrical tap and special tools required for the installation.

COMPLIANCE/CERTIFICATION



- ENERGY STAR® listed.
- UL certified.
- EMI/RFI emissions per FCC 47CFR Part 15B.
- RoHS compliant, contains no mercury or lead.
- Suitable for wet locations.

WARRANTY


- 5 years manufacturer warranty, consult support@runbisonlighting.com for more details.
- Terms and conditions may apply.



PHOTOMETRY



CIE 1931 x y Chromaticity Diagram



WARRANTY

This product is warranted for 5 years from the date of purchase. If this product does not perform to the specifications supplied on this package, send an email to support@runbisonlighting.com for product return and replacement. This replacement is the sole remedy available. Liability for incidental or consequential damage is expressly excluded.

