

Project

Catalog #

Prepared by

Notes

Order #

Date

LED PARKING LOT LIGHT


Wattage Selectable Led Parking Lot Light




DESCRIPTION

Robust and reliable, this LED product is a economical solution for your industrial applications. Constructed out of heavy duty die-cast aluminum with architectural baked polyester powder coating for lasting durability. Designed to replace the non-LED light fixture.

This product is UL & CUL certified. It is popular in side walk, parking lots, swimming pools, public area and other commercial area.








DIMENSION

Туре	MSB-100/150/200W-50K	MSB-100/150/200W-50K-SB	MSB-200/240/300W-50K	MSB-200/240/300W-50K-SB
Length(Inch)	18.2	18.2	22.7	22.7
Wight(Inch)	11.3	11.3	13.3	13.3
Height(Inch)	2.5	3.68	2.8	3.98
Weight(LB)	6.96	6.96	10.75	10.75

ORDERING INFORMATION

Series	MSB-100/150/200W-50K	MSB-100/150/200W-50K-SB	MSB-200/240/300W-50K	MSB-200/240/300W-50K-SB
CRI	>80	>80	>80	>80
Power	100/150/200W	100/150/200W	200/240/300W	200/240/300W
CCT	5000K	5000K	5000K	5000K
Lumens	13000-19500-26000LM	13000-19500-26000LM	26000-31200-39000LM	26000-31200-39000LM
Efficacy	130LM/W	130LM/W	130LM/W	130LM/W
Dimmable	0-10V	0-10V	0-10V	0-10V





CONSTRUCTION

• Unit includes heavy duty cast aluminum housing, LED array, heat sink, lens and gasket.

OPTICS

•Lumileds LED high luminous, greatly improve the light utilization and evenness •CRI 80+

DRIVER

•120-277V universal input voltage.

•0-10V smooth flicker free dimmable.

MOUNTING

• Multiple mounting methods with selected bracket option.

COMPLIANCE/CERTIFICATION

- UL & CUL listed.
- EMI/RFI emissions per FCC 47CFR Part 15B.
- RoHS compliant, contains no mercury or lead.
- Suitable for wet locations.



Optional Fittings

Optional Brackets (Sold Separately) and Installation Instructions

There are optional brackets for this fixture. The following is shoebox fixtures with different brackets.







WARRANTY

This product is warranted for 5 years from the date of purchase. If this product does not perform to the specifications supplied on this package, send an email to support@runbisonlighting.com for product return and replacement. This replacement is the sole remedy available. Liability for incidental or consequential damage is expressly excluded.

