

Catalog # Prepared by Notes Order# Date Project

DUAL HEAD HIGH POWER LED EMERGENCY LIGHT

Standard Red & Green Exit Sign

DESCRIPTION



A high-temperature thermoplastic housing protects against the worst elements, while LED lights require very little energy. Removable directional indicators are included with your Exit Sign. The LED exit sign is UL listed for damp locations, ideal for for installation in areas where the light will be exposed to occasional condensation or moisture.

All of our Emergency Light meet NFPA Life Safety Code 101, NED, OSHA and local codes. These commercial-grade emergency exit sign with lights ensures that your customers, employees, and visitors can quickly and easily find their way to safety in the event of a fire or other emergency.











5VAFlame Retardarit

SPECIFICATION FEATURES

Construction:

- Rugged, injection-molded UL rated 5VA flame retardant, hightemperature thermoplastic housing
- Tool-less access provided for easy maintenance, universal J-box mounting pattern provided for simple installation.
- Optional Red and Green Letters.

Illumination:

- Red version contains 12pcs long-lasting, efficient, ultra-bright LEDs
- Green version contains 6pcs long-lasting, efficient, ultra-bright LEDs

Electrical:

- Dual 120/277 voltage, 60Hz input
- Charge rate/power "ON" LED indicator light and magnetic test switch for mandated code compliance
- Built-in 1.2V 700mAH maintenance-free, rechargeable Ni-Cd battery that provides a minimum emergency duration of 90 minutes.
- Maximum 24 hour for full recharge time
- Operation temperature:0°C to 40°C / 32°F to 104°F.
- Suitable for Damp location.

WARRANTY

This product is warranted for 5 years for all electronic and housing and 2 years for battery from the date of purchase. If this product does not perform to the specifica-tions supplied on this package, send an email to support@runbisonlighting.com for product return and replace-ment. This replacement is the sole remedy available. Liability for incidental or consequential damage is expressly excluded.

